

Crown XLS-1502 Power Amp



Class D amp with Crown's ultra-efficient DriveCore technology weighs less than 11 lb

Higher DSP capabilities: More control; has band pass filter per channel

Increased lighting functionality; turn off all LED indicators except clip and thermal to reduce distraction in dark venues

Selectable input sensitivity; 1.4Vrms and .775Vrms options so that amp can be driven at full power

Set sleep mode after specified time without having to press a button

Security setting disables menu buttons; menu locked/unlocked by entering combination

System reset allows factory settings to be restored

Remote power trigger

Peakx™ Limiters provide maximum output while protecting your speakers

XLR, 1/4", RCA inputs provide flexibility

Integrated PureBand™ Crossover System for better performance and control

Efficient forced-air fans prevent excessive thermal buildup

Sensitivity 1.4Vrms

Frequency Response +0dB, -1dB

Signal to Noise >103dB (at .775Vrms, 6dB lower)

Intermodulation Distortion < 0.3%

Damping Factor > 200

THD < 0.5%

Crosstalk At 1kHz: > 85dB, At 20kHz: > 55dB

Dimensions 19" (48.3 cm) x 3.5" (8.9 cm) x 7.7" (19.6 cm)

Weight 8.6 lbs (3.9 kgs)

UPC 691991001000

300 watts 8 ohms dual, 525 watts 4 ohms dual, 775 watts 2 ohms dual, 1050 watts 8 ohms bridged, 1550 watts 4 ohms bridged

[Crown XLS Series 2 Manual](#)