

JBL Control 1 Pro Passive Loudspeaker Pair



(Priced As A Pair, Sold In Pairs Only)

Features:

- 150 Watts Continuous Power Handling
- Professional Drivers and Crossover Network
- Included Mounting Bracket
- Transparent and Faithful Sonic Performance
- Magnetically Shielded Transducers
- SonicGuard™ Overload Protection
- Available in Black or White Finishes

Specifications:

Frequency Range (-10 dB): 80 Hz to 20 kHz

Frequency Response (± 3 dB): 100 Hz – 18 kHz

Power Capacity: 150 W

Sensitivity: 87 dB SPL, 1 W, 1 m (3.3 ft)

Maximum SPL: 108 dB continuous, 114 dB peak

Directivity Factor (Q): 6.0

Directivity Index (DI): 7.8

Nominal Impedance: 4 ohms

Crossover Frequency: 4.2 kHz

Overload Protection: Full-range SonicGuard™ power limiting to protect network

and transducers

LF Drivers: 135 mm (5.25 in) low frequency loudspeaker

HF Drivers: 19 mm (.75 in) polycarbonate dome tweeter

Input Connectors: Spring-loaded terminals

Enclosure Material: Polypropylene Structural Foam

Finish: Black (C1Pro)

Dimensions: 235 mm x 159 mm x 143 mm (9.3 in x 6.3 in x 5.6 in)

Net Weight (ea.): 1.8 kg (4 lb)

Shipping Weight (pair): 4.6 kg (10 lb)

Included Accessories: Mounting Bracket Assembly

Optional Accessories: MTC-1A ultra-duty mount bracket MTC-8 heavy-duty mounting bracket

UPS 050036903455

[Control1 Pro Manual](#)