

Shure BLX24R/B58-J11 Wireless Handheld System



System Features

- Up to 12 compatible systems per frequency band (region dependent)
- One-touch QuickScan frequency selection quickly locates the best open frequency in case of interference
- Up to 14 hours of continuous use from 2 AA batteries (included)
- Up to 300 ft (91 m) operating range for total wireless freedom
- XLR and $\frac{1}{4}$ " output connectors
- Rugged and reliable Shure construction
- Legendary Shure microphones options featuring integrated microphone capsule design

Featuring an integrated BETA 58A® microphone cartridge, the BLX2/B58 Handheld Wireless Microphone Transmitter delivers wireless audio with professional clarity and reliability.

Offers up to 14 hours of continuous battery life with 2 AA batteries

Includes BLX2/B58, microphone clip, 2 AA batteries, and user guide

Rack-mountable and featuring rugged metal construction, the BLX4R offers simple setup and intuitive controls. One-touch QuickScan frequency selection quickly locates the best open frequency in case of interference. Removable antennas allow for quick antenna distribution. For use with BLX® Wireless Systems.

Rack mount kit included.

Features:

XLR and $\frac{1}{4}$ " output connectors

Microprocessor-controlled internal antenna diversity

Two-color audio status indicator LED

Green: Normal audio levels

Red: Excessive audio levels (overload / clipping)

Adjustable output level

LCD display with detailed RF and audio metering

UPC 042406555494

[BLX Wireless Manual](#)

CONSUMER ALERT Most users do not need a license to operate this wireless microphone system. Nevertheless, operating this microphone system without a license is subject to certain restrictions: the system may not cause harmful interference; it must operate at a low power level (not in excess of 50 milliwatts); and it has no protection from interference received from any other device. Purchasers should also be aware that the FCC is currently evaluating use of wireless microphone systems, and these rules are subject to change.