

TASCAM US-4X4 Computer-Tablet Audio Interface



US-4x4

Sampling frequency
Quantization bit rate
Analog audio inputs

MIC IN

Connector
Input impedance
Nominal input level
GAIN:MAX
GAIN:MIN
Maximum input level
(GAIN:MIN)
Gain

INST IN

Connector
Input impedance
Nominal input level
GAIN:MAX
GAIN:MIN
Maximum input level
(GAIN:MIN)

IN 1-4
XLR-3-31

IN 1-2
6.3mm(1/4")
(When set

Gain
LINE IN
Connector IN 1-4
6.3mm(1/4") TRS
(When set to

Input impedance
Nominal input level
GAIN:MAX
GAIN:MIN
Maximum input level
(GAIN:MIN)

Gain
Analog audio outputs
LINE OUT
Connector 6.3mm(1/4") TRS
Output impedance
Nominal output level
Maximum output level

PHONES
Connector 6.3
Maximum output level 45mW+45mW o
(THD+N 0.1% or less,

MIDI IN / OUT
Connector
Format
USB
Connector
Format
Power
When connected PC
When connected iOS
Power consumption 5W
Dimensions 11.62" W x 2.56"
(296mm W x65mm H
3.53lb (1.6

Weight
Operating temperature
Bundled software

Accessories AC adapter(GPE248-120200-Z), USB cable, SONAR X3 LE license card

Audio performance

Frequency response

LINE OUT(BALANCED)

44.1k/48k Hz

20Hz to 20kHz, +0dB/-0.1dB

88.2k/96k Hz

20Hz to 40kHz, +0dB/-0.2dB

PHONES

44.1k/48k Hz

20Hz to 20kHz, +0dB/-0.5dB

88.2k/96k Hz

20Hz to 40kHz, +0dB/-2dB

THD

0.003% or less

S/N ratio

101dB or more

Crosstalk

95dB or more

EIN

-127dBu or less

Computer system requirements

Windows

OS Windows 7(32-bit SP1, 64-bit SP1), Windows 8.0(32-bit, 64-bit),
of the latest OS version, please click [here](#).

Compatible computers Windows-compatible computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster (x86)

Memory 2GB or more
DRIVER ASIO2.0, WDM(MME)

Macintosh

OS OS X Mountain Lion(10.8), OS X Mavericks(10.9)* For further info

Compatible computers Apple Macintosh computer with a USB 2.0 port

CPU type/speed Dual core/2 GHz or faster

Memory 2GB or more

DRIVER Core Audio, Core MIDI

iOS

OS iOS 7* For more information about the OS compatibility on each m

UPC 043774031016